D-TEC LED

STANDARD

RoHS compliant | UL LISTED | ip68 | Cuttable

3K

5K

RGB

Single color Red

Single color Blue

Single color Green

APPLICATIONS

The 5050RL series is a flexible LED rope light that is the perfect solution for a wide variety of architectural and accent lighting applications including cove lighting, under-cabinet lighting, back-lighting, pathway lighting and decorative lighting. We offer 6 sku's in red, blue, green, 3K white,5K white and RGB. This rope light has an IP67 rating and can be installed indoor and outdoor.

FEATURES

* LED size: 5050
* Power: 2.4W / ft
* Length per unit cutting point: 19"
* High luminous efficiency >70 lm/W Avg, energy saving more than 80% of the energy cost of electricity use.
* Green environmental protection:no ultraviolet and infrared radiation, comply with RoHS requirements.
* No stroboscopic: fast starting , flicker-free, protects your eyes.
* Installation (embedded) is simple, flexible to meet different needs.
* Uniform lighting with no spot.
* Working hours: 50,000 hours

WARRANTY & DETAILS

* Input voltage: AC 110V
* Energy grade A
* Power Consumtion: 8 watts per meter (3.3ft)
* Illumination Angle 120°
* IP68
* UL Listed
* 3-year warranty
* Lead free technology (ROHS)
* Working temperature -13F to 113 F
* Working Humidity: 5% -100%

ACCESSORIES

* Additional clips for install
* Additional power lead: DTH-RL-PWR
* Additional controller + power lead for RGB: ...DTH-RL-RGB-PWR

ORDERING INFORMATION

PART #	LED	Lumens per foot	Lumens per watt	POWER	Lumens per roll	Roll Length
DTH-5050RL-RED	n/a	168	>70	2.4 W/ FT – 396 W per roll	27720	165 Ft
DTH-5050RL-BLUE	n/a	168	>70	2.4 W/ FT – 396 W per roll	27720	165 Ft
DTH-5050RL-GREEN	n/a	168	>70	2.4 W/ FT – 396 W per roll	27720	165 Ft
DTH-5050RL-RGB	n/a	168	>70	2.4 W/ FT – 396 W per roll	27720	165 Ft
DTH-5050RL-3K	3000K	168	>70	2.4 W/ FT – 396 W per roll	27720	165 Ft
DTH-5050RL-5K	5000K	168	>70	2.4 W/ FT – 396 W per roll	27720	165 Ft