

# GCP1070-70W-TCP

## LOW PROFILE CANOPY LIGHT



### STANDARD



### APPLICATIONS

This low profile parking garage canopy LED series can be widely used in outdoor lighting (wet location). It is Kelvin selectable 3K, 4K, 5k and wattage selectable 40W, 60W and 70W. Ideal for canopies, loading docks, parking garage, buildings, industrial areas, sidewalks, schools and many additional applications. The premium optics design greatly improves this light's coverage area.

### FEATURES

- \* **Color temperature tunable : 3K, 4K and 5K**
- \* Philips Lumileds 2835
- \* **Wattage selectable: 40W / 60W / 70W**
- \* Lumens: 120 Lm/W
- \* 4800 Lumens at 40W; 7200 Lumens at 60W and 8400 Lm at 70W
- \* Universal 100-277V AC input voltage
- \* Dimmable with 0-10V
- \* 135 degrees beam angle
- \* Light fixture and finish endurance tested to withstand 3000 hours of elevated ambient salt fog conditions as defined in ASTM Standard B 117
- \* Die Cast aluminium housing with durable dark bronze powder coat paint. Clear stripped PC diffuser
- \* High efficiency LED Driver
- \* Power factor > 0.90
- \* Total harmonic distortion <20%
- \* Color rendering Index >80

### ORDERING INFORMATION

PART #	CCT Color Temp	Lumens	Lumen/watt	Wattage Selectable
GCP1070-70W-C-H-TCP	3000K	4,800	120	40W
	4000K	7,200	120	60W
	5000K	8,400	120	70W



### WARRANTY & DETAILS

- \* ETL Listed
- \* DLC Listed
- \* Wet Location
- \* 5-year warranty on all electronics and housing
- \* -40 F to 104 F operating temperature.

### DIMENSIONS

