



Certified LED Lights®

STANDARD



APPLICATIONS

This CLL-MWP06 is an architectural outdoor rated, high-performance LED fixture designed to work in emergency egress lighting and general area lighting applications. This die-cast aluminum fixture comes standard with built in photocell to serve as an AC powered dusk to dawn light, an emergency egress light, or a switched unit which makes this light one of the most versatile emergency egress lights on the market.

FEATURES

- * Can be used as a Normally ON or Normally Off fixture as well as on a switched circuit
- * Offers long lasting, efficient, ultra bright white LED's.
- * 15 watt LED - 5000K -1801 Lumens @ 129 Lu/W
- * Mirror-bright reflector and prismatic polycarbonate refractor
- * Photocell control sensor included as standard for use as dusk-to-dawn fixture
- * Can be used as a Normally ON or Normally Off fixture as well as on a switched circuit
- * Phillips Lumiled SMD2835
- * Universal Dual 120V/277 voltage
- * Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- * Maintenance free, rechargeable NiCd battery
- * Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 5W 90-minute emergency illumination
- * Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hrs.


WARRANTY / LISTING

- * UL Listed for damp locations (-40°F – 113°F)
- * DLC premium
- * Five year warranty on all electronics and housing. Battery prorated for five year

MOUNTING

- * Universal knockout pattern on back plate for wall mount
- * Treaded opening at the top of the enclosure for conduit mount

DIMENSIONS



HOUSING

- * Decorative, low profile, architectural design.
- * Die-cast aluminum housing
- * Durable powder-coated finish in dark bronze
- * Sealed and gasketed

ORDERING INFORMATION

PART #	Lu/W	Power	Lumens	Voltage	Emergency
CLL-MWP06	129	15W	1801	120 – 277V	5W for 90 min