



## STANDARD



### APPLICATIONS

The Slim Canopy LED series can be widely used in outdoor lighting (wet location). Ideal for canopies, loading docks, parking garage, buildings, industrial areas, sidewalks, schools and many additional applications. The premium optics design greatly improves this light's coverage area.

### FEATURES

- \* Standard in 5000K
- \* 45W model is 115 Lm/W , 5180 Lumens
- \* 70W is 114 Lm/W, 8020 Lumens
- \* Universal 100-277V AC input voltage
- \* Long-life LEDs with 50,000 hours of operation
- \* Dimmable with 0-10V
- \* Light fixture and finish endurance tested to withstand 3000 hours of elevated ambient salt fog conditions as defined in ASTM Standard B 117
- \* Die Cast aluminium housing with durable dark bronze powder coat paint
- \* High efficiency LED Driver
- \* Power factor > 0.90
- \* Total harmonic distortion <20%
- \* Color rendering Index >80

### ORDERING INFORMATION

MODEL	Color Temp	Lumens	Lumen/watt	Wattage	Voltage
CLL-CN301D-45W-5K	5000K	5,180	115	45	100-277
CLL-CN301D-70W-5K	5000K	8,020	114	70	100-277

### WARRANTY & DETAILS

- \* UL listed
- \* DLC Listed
- \* Meets FCC Part 15 standards
- \* Suitable for Wet Location Application
- \* 5-year warranty on all electronics and housing
- \* -40 F to 122 F operating temperature.

### DIMENSIONS

