



## STANDARD



## APPLICATIONS

Light-sensitive photocell switches direct fixtures to turn off when ambient light is present, and switches them on when ambient light is absent. Ideal for use with outdoor light fixtures requiring photoelectric automation. Rain-tight for outdoor use. Preset time delay prevents unintended switching from flashes due to headlights, lightning and other temporary lighting sources.

## FEATURES

- \* Photocell sensor for traditional glass wall packs
- \* Heavy-duty, weatherproof, polycarbonate housing & lens
- \* Photocell is ½" diameter CDS (cadmium-sulfide)
- \* 100-277VAC voltage (50-60Hz) is standard
- \* Preset 30-60 second time delay
- \* Contact position at night is normally closed
- \* Power consumption: Below 1.5 watt average
- \* Light level: ON: 9 to 1.9 FC OFF: 2.8 to 5.6FC
- \* Thermal switch
- \* Tungsten rating: 150W, 1.20 Amp

## ORDERING INFORMATION

PART #	Input Voltage	Rated load	type
CLL-SWCHPC-100-277V	120V	150W	Recessed flush mount



## WARRANTY & LISTINGS

- \* cULus listed
- \* Suitable for ambient temperatures ranging from -40°F to 158°F, 96% relative humidity
- \* 5-year warranty on all electronics and housing

## WIRING

