



STANDARD



The CLL-MPAL series is a group of premium architectural LED area lights designed to illuminate parking areas, pathways, building facades, loading docks, and a wide variety of other large, general site lighting applications. Multiple mounting options make the MPAL a versatile luminaire for flood lighting, pole, ground and wall-mounted area lighting and other outdoor lighting requirements.

FEATURES

- * Available in 5000k color temperature
- * 140 LPU = 14,000 Lumens at 5000K
- * Long-life LEDs provide 30,000 hours of operation with at least 70% of initial lumen output (L70)
- * Beam angle 60x120
- * Universal 120-277 AC voltage (50-60Hz) is standard
- * Power factor > 0.90
- * Total harmonic distortion < 20%
- * Color rendering index > 80
- * Die cast aluminum housing with durable, dark bronze powder coat finish
- * Wireway enclosure is sealed with a water-tight, silicon rubber gasket
- * Easy installation in new construction or retrofit applications

ACCESSORIES

- * Optional spike-mount (CLL-LNDSL-BS) for ground mounting
- * Optional canopy-mount (CLL-LNDSL-CNY-KIT) for attachment to flat surface.

ORDERING INFORMATION

| PART # | Color Temp | Lumens | Lumen/watt | Watt |
|------------------|------------|--------|------------|------|
| CLL-MPAL-100W-5K | 5000K | 14,000 | 140 | 100 |

WARRANTY & DETAILS

- * IP65 rated
- * Lens is IK 8 rated for protection from external impacts
- * Complies with FCC Part 15, class B
- * 5-year warranty on all electronics and housing

MOUNTING OPTIONS

- * Aluminum die-cast knuckle-mount option for installation on a junction box. Includes 1/2" NPS stem with

DIMENSIONS

